

Model: AHC5522CTZ
Product Description

Type: Reciprocating Compressors
Application: HBP/AC - Air Conditioning
ProductDescription: R-407C
Voltage/Frequency: 440V 3~ 60Hz 400V 3~ 50Hz
Version: N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
EN12900	440V 3~ 60HZ	17406	4386	5100	2129	8.18	2.06	2.4	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)
EN12900	400V 3~ 50HZ	14997	3779	4394	2129	7.04	1.78	2.06	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 30
Weight Unit of Measure: KG
Displacement (cc): 39.95
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 1330

Electrical

Voltage Range (50 Hz): 340-440
Voltage Range (60 Hz): 396-499
Locked Rotor Amps (LRA): 25
Rated Load Amps (RLA 50 Hz): 3.7
Rated Load Amps (RLA 60 Hz): 3.5
Max. Continuous Current (MCC in Amps): 7.2

Motor Resistance (Ohm) - Main:	6.3
Motor Resistance (Ohm) - Start:	6.3
MotorType:	3PH
Overload Type:	
Relay Type:	

Agency Approval

CE Listed, GOST RUSSIA Listed, GOST UKRAINE Listed