# SARTY DATA SHREET RU

SDS PF-16-GB Issue 1, Version 3, Revised 26 September 2016 **Total Pages: 6** 

DiversiTech

## **Diversi-Flush**

## SECTION 1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY

1.1 Product identifier

Diversi-Flush

#### 1.2 Relevant identified uses of the substances or mixture and uses advised against

HVAC System Flushing Solvent.

Uses advised against: Any applications other than those specified above.

## 1.3 Details of the supplier of the safety data sheet

DiversiTech UK Limited Glaisdale Drive East Nottingham NG8 4LY United Kingdom Tel: +44 1159005858 Fax: +44 1159294468

## 1.4 Emergency telephone number

Emergency tel: 001 +1813 248 0585, 24 Hours, 7 Emergency Days, Chem-Tel, Inc.

### **SECTION 2. HAZARDOUS IDENTIFICATION**

#### 2.1 Classification of the mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

#### GHS Classification:

Acute Toxicity Oral Category	4
Acute Toxicity Inhalation Category	4
Eye Irritation Category	2B

2.2 Label Elements:



Signal Word: Warning!

#### Hazard Statement(s)

H302	Harmful if swallowed.
H320	Causes eye irritation.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary Statement(s)

P102 P103 P261 P264 P270	Keep out of reach of children. Read label before use. Avoid breathing fumes or vapours. Wash thoroughly after handling. Do not eat.drink, or smoke when using this product.
P270 P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves, eye protection, face protection.
P312	Call your national POISON CENTRE information service or a doctor if you feel unwell.
P301+312	IF SWALLOWED: Call your national POISON CENTRE information service or a doctor if you feel unwell.
P330	Rinse mouth.
P304+340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + 351 + 338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + 313	If eye irritation persists: Get medical attention.
P391	Collect spillage.
P501	Dispose of contents in accordance with the international and local regulations.

# SAFETY DATA SHIFT EU

## **Diversi-Flush**

## SECTION 2. HAZARDOUS IDENTIFICATION (cont.)

2.3 Other Hazards:

 Workplace exposure limit:
 This product does not have a workplace exposure limit.

 PBT:
 This product does not contain substances identified as PBT or vPvB.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances
----------------

Name:	CAS Number	EINECS Number	% Composition	Classification according to CHIP
Acetone	67-64-1	200-662-2	1-10	H225: Highly flammable liquid and vapour Category 2 H319: Causes serious Eye irritation Category 2A H401: Toxic to aquatic life. Category 2
Tert-Butyl Acetate (*WEL)	540-88-5	208-760-7	10-30	H226: Flammable liquid and vapour Category 3 H336: May cause drowsiness or dizziness Category 3
Trans-Dichloroethylene	156-60-5	205-860-2	50-70	H225: Highly flammable liquid and vapour Category 2 H332: Harmful if inhaled.Category 4 H412: Harmful to aquatic Category 3
Ethyl Nonafluorobutyl Ether	163702-05-4	98-02-0209-00	1-10	H226: Flammable liquid and vapour Category 3

DIVERSITECH

#### 3.2 Mixtures

No further information

#### **SECTION 4. FIRST AID MEASURES**

#### 4.1 Description of first aid measures

Skin contact - Wash skin with soap and water for at least 15 minutes if irritation develops or persists, get medical attention. Eye contact - Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing lifting lower and

upper cyclic occasionally. If irritation persists, get medical attention. Ingestion – Rinse mouth. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Call your national POISON CENTRE information service or doctor for medical advice.

Inhalation - Remove person to fresh air and keep comfortable for breathing. If not breathing give artificial respiration. Get medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

Harmful by inhalation and ingestion. Inhaling the product may have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Arrhythmia (deviation from normal heart beat). May cause drowsiness and dizziness. Irritating to eyes and skin. There may be irritation and redness at the site of contact. Swallowing can cause gastro-intestinal irritation, nausea, vomiting and diarrhea. When ingested there may be soreness and redness of the mouth and throat.

4.3 Indication of any immediate medical attention and special treatment needed

If the product is ingested or inhaled immediate medical attention is required.

## **SECTION 5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

Foam, Carbon dioxide extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

#### 5.2 Special hazards arising from the substance or mixture

In combustion emits toxic fumes. Contact with certain finely divided reactive materials may result in formation of explosive or exothermic reactions under specific conditions. In the event of a liquid spill ethyl nonafluoroisobutyl ether and ethyl nonafluorobutyl ether will evaporate from the mixture faster than the other components, leaving a mixture enriched with trans-1, 2-dichloroethylene, acetone and t-butyl acetate. The enriched mixture may be flammable. Exposure to temperatures above 70°C/160 °C may cause containers to burst.

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. Use water spray to keep fire-exposed containers cool and to knock down vapours that may result from product decomposition.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions

Remove contaminated clothing immediately. Keep unnecessary and unprotected people away from area of spill Mark out the contaminated area with signs and prevent access to unauthorized personnel. Keep spark, flames and heat sources away from spill. Ventilate area of leak or spill. Only personnel equipped with proper respiratory (organic vapour cartridge) and eye/skin protection (neoprene or nitrile gloves and aprons or coveralls; neoprene or urethane boots) should be permitted in the area until air has been tested and determined safe, including low lying areas.

#### 6.2 Environmental precautions

Do not discharge into drains or rivers. Contain the spillage.

6.3 Methods and material for containment and cleaning up

Absorb and contain liquid with clay, vermiculite or other inert substance and package in a recovery drum or other suitable container for disposal.

# SAFETY DATA SHIFT FU

## **Diversi-Flush**

## SECTION 6. ACCIDENTAL RELEASE MEASURES (cont.)

6.4 Reference to other sections Please refer to Section 8 for details on protective wear.

### **SECTION 7. HANDLING AND STORAGE**

#### 7.1 Precautions for safe handling

Protect from physical damage. Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Wash hands after handling.

DIVERSITECH

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool dry ventilated area away from sources of extreme heat moisture and incompatibilities; in an area kept below 45 °C. If container temperature exceeds 41 degrees Celsius, cool the can with water before opening cans or filling injector to minimize the risk of splashing or hazardous contact. Do not pierce or burn, even after use. Close container and/or injector valve tightly after use and when empty.

#### 7.3 Specific end use(s):

HVAC System Flushing Solvent. Industrial section specific solution: None.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

TERT-BUTYL ACETATE UK - 8 hour TWA: 966 mg/m<sup>3</sup> UK - 15 min. STEL: 1210 mg/m<sup>3</sup>

ACETONE UK - 8 hour TWA: 1210 mg/m<sup>3</sup> UK - 15 min. STEL: 3620 mg/m<sup>3</sup>

### 8.2 Exposure controls

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. **Eye/face protection:** Use chemical safety goggles and/or a full face shield where splashing is possible. Ensure eye bath is to hand. **Skin protection:** 

Hand protection: Butyl rubber gloves. Neoprene gloves. Nitrile gloves.

Other: Wear solvent resistant gloves made of neoprene, nitrile or butyl rubber to minimise skin contact. Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Thermal hazards: Not relevant

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

Appearance Odour Odour Threshold: pH value: Melting Point (Pour Point): Initial boiling point and boiling range: Flash Point: Flammability limits: Auto/Self-ignition temperature: Decomposition temperature: Decomposition temperature: Relative density Vapour density Evaporation rate Solubility Partition coefficient (n-octanol/water): Viscosity Explosive properties: Oxidising properties:	Colourless liquid Sweet-smelling No data available $21^{\circ}$ C: ~ 1 psig, ~ 16psia $41^{\circ}$ C Does not exhibit a flash point as defined by ASTM D93 Pensky-Martens Closed Cup Test. No data available No data available No data available No data available No data available (Ether = 1): > 1 ~ 7 grams per L in water No data available No data available
---	---

#### 9.2 Other information

No further relevant information available.

# SAFETY DATA SHIFT EU

## **Diversi-Flush**

## SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity

Stable under normal conditions.

10.2 Chemical stability

Stable under normal conditions.

**10.3 Possibility of hazardous reactions** Carbon Dioxide. Carbon Monoxide. Hydrogen sulphide. Phosgene gas.

10.4 Conditions to avoid
Heat. Incompatibles.
10.5 Incompatible materials
Avoid contact with strong oxidizing agents, strong alkalis and strong acids.
10.6 Hazardous decomposition products
Carbon Dioxide. Carbon Monoxide. Phosgene gas.

## SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects Potential health effects:

11.1.1 Acute Toxicity: Harmful by inhalation and ingestion. Inhaling the product may have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Arrhythmia (deviation from normal heart beat). May cause drowsiness and dizziness.

DIVERSITECH

Oral toxicity (rat) LD50: 1,235 mg/kg (trans-dichloroethylene)

11.1.2 Irritation: If in contact with eye, there may be irritation and pain.

11.1.3 Corrosive: Non-Corrosive.

11.1.4 Sensitisation: Not expected to be a sensitizer.

11.1.5 Repeated dose toxicity: Repeated exposure may cause skin dryness or cracking.

11.1.6 Carcinogenicity: Not expected to be carcinogenic.

**11.1.7 Mutagenicity:** Not expected to be mutagenic.

11.1.8 Toxicity for reproduction: Not expected to be toxic to reproduction.

11.1.9 Route of exposure: Inhalation

**11.1.10 Symptoms related to the physical, chemical and toxicological characteristics:** Inhaling the product may have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Arrhythmia (deviation from normal heart beat). May cause drowsiness and dizziness.

## SECTION 12. ECOLOGICAL INFORMATION

12.1 Toxicity
No data.
12.2 Persistence and degradability
Not biodegradable
12.3 Bioaccumulative potential
Bioaccumulation potential.
12.4 Mobility in soil
Readily absorbed into soil.
12.5 Results of PBT and vPvB assessment
This substance is not identified as a PBT substance.
12.6 Other adverse effects
Toxic to aquatic organisms. Toxic to soil organisms.

## SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

**Disposal operations -** Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. **Disposal of packaging -** Ensure that containers are empty before discarding.

Please follow all local, regional, national and international laws.

# SAFETY DATA SHEFT EU

## **Diversi-Flush**

## SECTION 14. TRANSPORTATION INFORMATION

This product is eligible to ship as Limited Quantity by ground and ocean.

14.1 UN-Number

LIN 3082

14.2 UN proper shipping name

Environmentally hazardous substance, liquid, N.O.S. (contains Ethyl Nonafluorobutyl Ether, Ethyl Nonafluoroisobutyl Ether and trans 1,2 Dichloroethylene)

DIVERSITECH

14.3 Transport hazard class(es)

Class 9 14.4 Packing group Ш 14.5 Environmental hazards Environmentally Hazardous Substance 14.6 Special precautions for user See section 8 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable to packaged goods

### Mode-specific information:

ROAD/RAIL (ADR/RID/CDG)	Transport category 3
	Tunnel restriction code
SEA (IMDG)	Marine Pollutant
	EmS: F-A S-F
AIR (ICAO/IATA)	ERG Code 9L

Goods packed in combination packages with inner packaging's containing a maximum of 5 litres can be carried under the Limited Quantities provisions of the road and sea regulations.

## **SECTION 15. REGULATORY INFORMATION**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Е

The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

#### 15.2 Chemical safety assessment

A chemical safety assessment has not been conducted.

### **SECTION 16. OTHER INFORMATION**

Other information

This safety data sheet is prepared in accordance with Regulation (EC) No 1272/2008 (CLP).

Revision Summary: All Sections: New GHS Format

#### Abbreviations:

UN Model Regulations means the Model Regulations annexed to the most recently revised edition of the Recommendations on the Transport of Dangerous Goods published by the United Nations. IMDG Code means the International Maritime Dangerous Goods code, as amended. ADR means the European Agreement concerning the International Carriage of Dangerous Goods by Road, as amended. RID means the Regulations concerning the International Carriage of Dangerous Goods by Road, as amended. ADN means the European Agreement concerning the International Carriage of Dangerous Goods by Road, as amended.

# SAFEY DATA SHIFT EU

## **Diversi-Flush**

## **SECTION 16. OTHER INFORMATION (cont.)**

#### Sources of Key Data:

UK Regulatory References: The Control of Substances Hazardous to Health Regulations 2002 (as amended 2004). European Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures. Approved Code of Practice: Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. British Workplace Exposure Limits EH40. Classification and Labelling of Clabelly, Harmonized System of Classification and Labelling of Chemicals (CHS).

DIVERSITECH

Classification and Labelling Guidance: Globally Harmonized System of Classification and Labelling of Chemicals (GHS), Annex 2 Precautionary Statement and Pictograms: Globally Harmonized System of Classification and Labelling of Chemicals (GHS), Annex 3 Guidance on the Preparation of Safety Data Sheets: Globally Harmonized System of Classification and Labelling of Chemicals (GHS), Annex 4

## IMPORTANT:

The information presented herein, while not guaranteed, was prepared by competent technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SUITABILITY, STABILITY OR OTHERWISE. The information included herein is not intended to be all-inclusive as to the appropriate manner and/or conditions of use, handling and/or storage. Factors pertaining to certain conditions of storage, handling, or use of this product may involve other or additional safety or performance considerations. While our technical personnel will be happy to respond to questions regarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended to, and nothing herein shall be construed as a recommendation to, infringe any existing patents or violate any laws, rules, regulations or ordinances of any governmental entity.